
RECEIVED
CENTRAL FAX CENTER

MAY 0 4 2005



311 South Wacker Drive, 53rd Floor Chicago, Illinois 60606-6630

phone: 312-554-3300 fax: 312-554-3301 www.wwrfirm.com

FACSIMILE TRANSMITTAL SHEET	
TO:	rrom:
Examiner Derek Boles	Peter M. Siavelis, Esq.
COMPANY:	DATE:
U.S. Patent and Trademark Office	May 4, 2005
fax number: 703-872-9306	TOTAL NO. OF PAGES INCLUDING COVER:
YOUR REFERENCE NUMBER:	SENDER'S REFERENCE NUMBER:
10/756,820	5915 P 005
RE: Attached	

This fax may contain Attorney work product, which is privileged and confidential

NOTES/COMMENTS:

Should you have any problems with receipt of this facsimile transmission, please contact Gillian Gardner at (312) 435-7259.

Attorney Docket No. 5915 P 005 Inventor(s): James M. Bettridge et al.

Application No. 10/756,820 Filed: January 13, 2004

For: Cabinet for Computer Devices with Air Distribution Device

Attachment:

Proposed Amendments for Discussion, 4 pages

Attorney Docket No. 5915 P 005

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

James M. Bettridge et al.

Application No.:

10/756,820

Confirmation No.: 2373

Filed On:

January 13, 2004

Examiner:

Derek Boles

Art Unit:

3749

For: Cabinet for Computer Devices with Air

Distribution Device

PROPOSED AMENDMENTS FOR DISCUSSION WITH EXAMINER **** NOT FOR ENTRY ****

1. (Amended to include subject matter of allowable dependent claim 8) A cabinet for housing computer devices, the cabinet comprising:

an internal chamber defined by a side wall arrangement having at least a front wall;

a support structure configured to receive a plurality of computer devices, the support structure positioned within the internal chamber;

a substantially vertical duct defining a passageway for air distribution, the vertical duct positioned within the internal chamber, the vertical duct having a plurality of air discharge ports in fluid communication with the passageway, wherein each discharge port comprises an adjustable nozzle that can be selectively adjusted to control the quantity and direction of air flowing through the nozzle; and,

an inlet fan in fluid communication with the passageway, the inlet fan positioned within the internal chamber.